



Date: 18 September 2020

Quotation Number: _____

Project Reference Number: RFQ 2020 - 100

Name of the Project: Procurement of IEC Equipments/Materials for Office Productivity


Location of the Project: _____

REQUEST FOR QUOTATION

Company Name: _____

Address: _____

Please quote your lowest price on the item/s listed below, subject to the General and submit your quotation duly signed by your representative on or before 23 September 2020


EDGARDO S. PARE
Regional Director

Note:

1. The approved budget for the contract is P 752,699.60
2. All entries shall be submitted to PSA Bldg., DMGC, Maimpis, City of San Fernando, Pampanga or through e-mail at psaregion3@gmail.com
3. Price Validity shall be for a period of 30 calendar days.
4. For inquiries, contact the PSA-RO3-BAC Secretariat at (045) 455- 2552/ (045) 436 3806.

ITEM NO.	ITEM AND DESCRIPTION	QTY.	UNIT	UNIT PRICE	TOTAL AMOUNT
	Wireless Router	12	pcs		
	Wi-Fi Technology:				
	AC5400 MU-MIMO Tri-band Gigabit, 1000+2166+2166 Mbps				
	Key Features:				
	Tri-Band (5 GHz + 5GHz + 2.4 GHz)				
	4x4 AC, MU-MIMO				
	2 USB 3.0 Ports				
	Dual-Core CPU				
	Beamforming Technology				
	8 Adjustable Antennas				
	Smart Wi-Fi				
	Network Standards:				
	802.11b, 802.11a/g, 802.11n, 802.11ac				
	Wi-Fi Speed:				
	AC5400 (N1000 + AC2166 + AC2166)				
	Wi-Fi Bands:				
	2.4 and 5 GHz(2x) (simultaneous tri-band)				
	Wi-Fi Range:				
	Very Large Household				
	Number of Ethernet Ports:				
	1x Gigabit WAN port, 8x Gigabit LAN ports				
	Other Ports:				
	Two(2) USB 3.0 ports, Power				
	Antennas:				
	8x external adjustable antennas				
	Processor:				
	1.4 GHz dual-core				
	LEDs:				
	Status Indicator, MU-MIMO Indicators, illuminated Linksys logo, Wi-Fi, Wi-Fi Protected Setup, Power, Internet, LAN 1-8, USB 3.0, USB 2.0				
	Wireless Encryption:				
	64/128-bit WEP, WPA2 Personal, WPA2 Enterprise				
	Operation Modes:				
	Wireless Router, Access Point (Bridge)				
	Storage File System Support:				
	FAT, NTFS, HSF+				
	Easy Setup:				
	Browser-based Setup				
	Linksys Smart Wi-Fi Setup				
	Certified Operating Systems:				
	Windows 7, Windows 8.1				
	Minimum System Requirements:				
	Internet Explorer® 8, Safari® 5 (for Mac®), Firefox® 8, Google Chrome™				
	Dimensions (LxWxH):				

264.52 x 318.15 x 66.66 mm (10.41 x 12.53 x 2.62 in.) without antennas			
Weight:			
1727.7 g (60.94 oz)			
Security Features:			
WPA/WPA2, 128 bit AES link encryption, WEP			
Regulatory Compliance:			
FCC class B			
Power Supply:			
Input: 100-240V ~ 50-60Hz; Output: 12V, 5A			
WIRELESS ACCESS POINT		3	pcs
Specifications			
Dimensions	196.7 x 196.7 x 35mm		
Weight	350 g		
With Mounting Kits	450 g		
Networking Interface	(2) 10/100/1000 Ethernet Ports		
Port	(1) USB 2.0 Port		
Buttons	Reset		
Power Method	Passive Power over Ethernet (48V), 802.3af /8023at Supported (Supported Voltage Range: 44 to 57VDC)		
Power Supply	Uni Fi Switch (PoE)		
Power Save	Supported		
Maximum Power Consumption	9W		
Maximum TX Power			
2.4 GHz	22 dbm		
5 GHz	22 dbm		
Antennas	(3) Dual-Band Antennas, 2.4 GHz: 3 dBi, 5 GHz: 3 dBi		
Wi-Fi Standards	802.11 a/b/g/n/r/k/v/ac		
Wireless Security	WEP, WPA-PSK, WPA-Enterprise (WPA, WPA2, TKIP/AES)		
BSSID	Up to 8 per Radio		
Mounting	Wall/Ceiling(Kits Included)		
Operating Temperature	-10 to 70°C(14 to 158°F)		
Operating Humidity	5 to 95% Noncondensing		
Certifications	CE, FCC, IC		
Advanced Traffic Management			
VLAN	802.1Q		
Advanced QoS	Per-User Rate Limiting		
Guest Traffic Isolation	Supported		
WMM	Voice, Video, Best Effort, and Background		
Concurrent Clients	250+		
Supported Data Rates(Mbps)			
Standard	Data Rates		
802.11ac	6.5 Mbps to 1300 Mbps (MCS0-MCS9 NSS1/2/3, VHT 20/40/80)		
802.11n	6.5 Mbps to 40 Mbps (MCS0- MCS23, HT 20/40)		
802.11a	6,9,12,18,24,36,48,54 Mbps		
802.11g	6,9,12,18,24,36,48,54 Mbps		
802.11b	1,2,5.5,11 Mbps		
Uninterrupted Power Supply (UPS)		6	pcs
Specifications			
Output			
Output Power Capacity	325 Watts/625 VA		
Max Configurable Power	325 Watts/0 VA		
Nominal Output Voltage	230V		
Efficiency at Full Load	0.65		
Topology	Standby		
Waveform Type	Square wave		
Output Connections	(3) Universal Receptacle (Battery Backup)		
Efficiency at Half Load	0.76		
Input			
Nominal Input Voltage	230V		
Input Frequency	45-65 Hz		
Input Connections	IEC-320 C14		
Cord Length	1.22 meters		
Input voltae range for main operations	151-299V		
Maximum Input Current	3A		
Type of Input Protection Required	3-pole breaker		
Batteries and Runtime			

Battery Type	<i>Maintenance-free sealed Lead-Acid battery</i>		
Included Battery Modules	1		
Typical recharge time	6 hour(s)		
Surge Protection and Filtering			
Surge energy rating	273 joules		
Digital Audio Recorder		1	pcs
Specifications			
Record in MP3/LPCM with a high sensitivity 5-microphone.			
Up to C of built in storage, expandable via micro SD (SDHC/SDXC) cards.			
Focus and wide microphone modes to suit lectures of meetings.			
Direct USB built for easy connection to PC			
FM radio to listen to or record radio broadcast			
built-In Re-chargeable Battery.			
HDMI to HDMI Cable 5 Meters		34	pcs
Specifications			
In-wall- Series			
Fire resistant PVC jacket			
Supports Latest HDMI Standard			
4k,UHD,3D,Audio Return Channe (ARC), Category 2 Certified, 18Gpbs/600MHz			
100% Pure copper conductors, Triple Cable Shielding, 24K Gold-plated full metal			
Compatible with all HDMI Components: connects			
Mouse		72	pcs
Specifications			
Connection type :	2.4 GHz wireless connection		
Wireless Range:	33 feet (10 meters)		
Connect/Power:	Yes, On/Off switch		
Battey Type:	1 x AA		
DPI (min/max):	1000±		
Sensor Technology:	Yes, 2D, mechanical		
Sensor Resolution:	1000dpi		
Scroll Wheels:	Yes		
Number of Buttons:	3		
Standard and Special Buttons:	Middle Click		
Interface:	USB		
External Hard Drive		52	pcs
Specifications			
Storage Capacity:	2 TB		
Connection:	USB 3.0		
Plug and Play			
Operating System	Microsoft Windows 7, 8, 10		
	Mac OS X 10.7 or Linux Kernel 2.6.31 or later		
Shock protection system includes a silicone rubber case			
Lapel		1	pc
Tie Clip Lapel Condenser Microphone			
Material:	Copper microphone head		
Cable length:	Approx 1.5M		
Mic Length:	approx 28mm		
Audio cable plug connector:3.5mm			
Network Maintenance Tools			
Lan Cable		3	pcs
Cat 6 Ethernet Cable			
Length:	1000feet/box		
Number of Pairs:	4.00		
Total number of conductors:	8.00		
Stranding:	Solid		
Crimping Tool		1	pc
Stripper Cutting Ethernet Cable			
Fit RJ45, Cat6			
Cable Stripper		1	pc
RJ 45 connector		500	pcs
8 position, 8 contact pass through style data plug for solid or stranded cable			
gold plated contacts			

Network Switch Hub		4	pcs
24 x 10/100/1000 ports			
2 x gigabit SFP ports			
L2+ Static Routing			
Handheld Vacuum Cleaner		8	pcs
Watts	690.00		
Dirt Capacity	500 cc		
One touch power	on/off		
Cord	5 meters long		
Maintenance Tools Set		6	pcs
Includes, hammer, pliers, wrench, screw drivers, and other tools for minor			
Wireless Micropohone		4	pcs
Dual Channel UHF Wireless Microphone			
High Quality Sound			
High grade low noise microphone cable			
with case for easy to carry			
Signal and battery indicator			
with 4 x AA batteries			
with anti-slip rubber roller ring			
Wired microphone		8	pcs
Unidirectional Dynamic Vocal Microphone			
Precision-engineered microphone for lead vocal applications			
High grade low noise microphone cable			
Cord length: 15-20 meters			
with anti-slip rubber roller ring			
Digital camera/phone Tripod		2	pcs
Maximum versatility and lightweight			
Easy and portable for carrying and usage			
Maximum height: 6 feet			
Heavy Duty			
Digital Camera Tripod		1	pcs
Maximum versatility and lightweight			
Easy and portable for carrying and usage			
Maximum height: 6 feet			
Heavy Duty			
Canon EOS M50 Battery			
LP-E12 Battery		1	pcs
Battery type	Rechargeable Lithium-Ion		
Output	7.2V		
Capacity	875mAh		
Canon EOS 750D Battery			
LP-E17 Battery		1	pcs
Battery type	Rechargeable Lithium-Ion		
Output	7.2V		
Capacity	1040mAh		
Micro HDMI to HDMI		2	pcs
Ringlight		5	pcs
with Clip for PC			
USB Powered			
Adjustable light			

After having carefully read and accepted your General Conditions, I/We quote you on the item at price noted above.

NAME OF FIRM

 Signature Over Printed Name of
 Authorized Representative

 Contact Number

Date: _____