



REPUBLIC OF THE PHILIPPINES
PHILIPPINE STATISTICS AUTHORITY
Regional Statistical Services Office No. III

REQUEST FOR QUOTATION

The Philippine Statistics Authority Region III Bids and Awards Committee (BAC) will undertake a Negotiated Procurement- Small Value Procurement for the **Procurement, supply and delivery of 10 units LED projector**, in accordance with Section 53. 9 of the Implementing Rules and Regulations of Republic Act No. 9184. The details of the project are as follows:

Name of Project:	Procurement, supply and delivery of 10 units LED projector
Brief Description:	Procurement, supply and delivery of 10 units LED projector for Office Productivity of PSA Central Luzon RSSO and PSOs
Approved Budget for the Contract:	Php400,000.00

Interested bidders are required to submit their valid and current Mayor's Permit, DTI registration, copy of the BIR Certificate of Registration, PHILGEPS Registration Number, and duly accomplished Annexes A (Statement of Compliance to the Technical Specifications) and B (Financial Bid Submission Form).

Bidders may submit their quotation and eligibility documents through online or any electronic facilities at psaro3bac@gmail.com with password protection to ensure the security, integrity and confidentiality of the quotation. The password for accessing the files must be disclosed during the actual opening of quotation on **19 October 2020, 1:30 p.m.** through videoconference. The subject through online submission must be formatted as **<Name of Company_ Name of Project >**.

Bidders may also submit their quotation and eligibility documents at PSA RSSO III, Diosdado Macapagal Government Center, Maimpis, City of San Fernando, Pampanga. The envelope containing the quotation and eligibility documents **MUST be properly sealed, labeled and signed by the bidders**. It should be sealed (**DO NOT OPEN**) and labeled with the following details:

Name of Project
Name of the company
Name of Owner/Authorized Representative
Address
Contact details (including contact number and e-mail address)

Award of contract shall be made to the lowest quotation, which complies with the minimum description as stated above and other terms and conditions stated in the price quotation form. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative/s.

The deadline for submission of quotation and eligibility documents through manual or online submission is on **19 October 2020, 1:00 p.m.**

For inquiry, you may contact us at tel. no. 045-436-3806/045-436-4452 or e-mail us at psaro3bac@gmail.com.


ELNA RUTH F. CASASOLA
RBAC Chairperson

TECHNICAL SPECIFICATIONS

ITEM DESCRIPTION		Statement of Compliance
LED PROJECTOR (HDMI READY)		
Optical		
LCD Panel	0.63" (1.6cm) P-Si TFT x 3	
Resolution	XGA (1024x768)	
White light output (brightness)	4000 ANSI Lumens (Normal Mode)	
	2600 ANSI Lumens (Eco Mode)	
Brightness	4000 ANSI Lumens (Normal Mode)	
	2600 ANSI Lumens (Eco Mode)	
Contrast Ratio	125.00	
Lens	Manual Focus, Manual Zoom x 1.2	
Lamp Wattage	215W UHP	
Lamp Life	5000 hours (Normal Mode)	
	6000 hours (Eco Mode)*	
Diagonal Display Size	30~300" (76~762cm)	
Number of colours	8 Bit/colour, 16.7M colours	
Keystone correction	9:1 upward shift, fixed	
Focus distance	0.9m~9.0m (Wide), 1.0~10.7m (Tele)	
Distance to width ratio	1.5 (Wide), 1.8 (Tele)	
Compatibility		
Computer compatibility	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16"	
Composite/S-Video	NTSC, PAL , SECAM, PAL -M, PAL -N, NTSC4.43, 1125p(1080p@50/60), 750p(720p@50/60)	
HDMI Video	Signal: 525i(480i), 525p(480p), 625i(576i), 1125i(1080i@50/60), 750p(720p@50/60), 1125p(1080p@50/60)	
Plug & Play	DDC2B	
Features		
Speakers	16W Mono (8W x 2)	
Basic functions	Freeze, Magnifying, Blank, Auto adjustment, Search, Page Up & Down (for USB mouse function), Auto signal search, Auto eco mode	

ITEM DESCRIPTION		Statement of Compliance
Picture Adjustments	Aspect selection (video, data, HDMI), Equalizing Gamma Correction, Equalizing Color temperature adjustment, 2-3 pull down for NTSC, Mirror reverse image, upside down image, Progressive Scan, Noise Reduction, Overscan	
Digital keystone	Auto V keystone ± 30 degrees (@ XGA 60Hz)	
Advanced Features	MyScreen, My Memory, My Button, My Text, My Source, Picture mode (normal, cinema, dynamic, blackboard, whiteboard greenboard, photo), Daytime Mode, Input Source Naming (English), Resolution setting, Template, Closed Caption (for NTSC & component 480i only), Audio pass through, Framelock, Audio ports assign, Cloning, Drawing function (Optional wireless pen tablet TB-1 is necessary), Eco Mode (Normal, Eco, Intelligent Eco, Saver), iOS Connectivity	
Outward	Easy lamp replace from top, Air filter slides towards front side or top	
Power on & off	Direct on, Auto off	
Security Systems	Security bar, PIN-Lock, MyScreen Password, Keypad-Lock, Kensington slot, Transition detector, My Text, Security label	
Network	Network presentation (PC still/moving picture transfer), Campus Notification System, Configure and control projector via web browser, receive alerts via e-mail, projector management via SNMP, Crestron RoomView®, Scheduling, My Image, displaying text data transferred via the network, Command Control via network, A MX Device Discovery, PJ Link™, Network Bridge	
Connections		
Digital Input	1 x HDMI (HDCP compatible)	
Computer Input	2 x 15-pin Mini D-sub	
Monitor output	1 x 15-pin Mini D-sub (RCA combination)	

ITEM DESCRIPTION		Statement of Compliance
Video Input	2 x 15-pin Mini D-sub (shared with analogue computer in 1/2)	
	1 x RCA for composite	
	1 x Mini-DIN for S-Video	
Audio Input	2 x Stereo Mini Jack	
	1 x pair RCA (L/R)	
	1 x Microphone Jack (Stereo Mini)	
Audio Output	1 x pair RCA (L/R)	
USB Type A	2 x USB Type A (for PC-less presentation and wireless network)	
USB Type B	1 x USB Type B (for USB display or USB mouse control)	
Wired network	1 x RJ-45	
Wireless network	Option, IEEE802.11b/g/n ready (optional wireless adapter required)	
Control	1 x 9-pin D-sub for RS232C Control	
Power		
Power Supply	100-120V / 220-240V auto switching	
Power Consumption/Standby	300W/<0.5W (AC 220-240V)	
Physical		
Dimensions (W x H x D) (Without feet)	317x98x288mm (excluding feet and extrusions)	
Weight	3.6Kg	
Noise Level	35dB (Normal Mode)/31dB (Eco mode)	
Air Filter	Hybrid (up to 5000 hours)	
Miscellaneous		
MISCELLANEOUS	Indicator lights (lamp, temp, power), Ceiling mount image, Rear projection image, Serial number label on side, MAC PC support: PJ Control software, MAC address label on side, LiveViewer software	
Certification		
CERTIFICATION	UL60950-1/cUL, FCC Part 15 subpart B class B, CE Marking: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC Directive), EN60950-1 (Low voltage directive), WEEE, RoHS, ErP (lot6) compliant, DEMKO-GS, GOST-R	

ITEM DESCRIPTION		Statement of Compliance
ACCESSORIES SUPPLIED	Remote control with batteries (HL02881), Computer cable, Power cord, Lens cap, Security label, Adapter cover, User manual (detail & concise), Network & wireless software (CD-ROM)	
Warranty	2 years warranty	

Note: Bidders must state either "COMPLY" or "NOT COMPLY" in the column "Statement of Compliance" against each of the individual parameters of each specification stating the corresponding performance parameter of the service/equipment offered.

I hereby certify to comply with all the above Technical Specifications

Name of Company

Date: _____

Signature over Printed Name
Authorized Representative